
Page 1/10

*

*





Printing date 14.04.2017

Version number 161

Revision: 29.11.2016

Trade name: MOTIP	® SEMI GLOSS BLACK 500 ML
Article number: 0400 1.2 Relevant identifie Sector of Use	l d uses of the substance or mixture and uses advised against
SU21 Consumer user SU22 Professional u	s: Private households / general public / consumers ses: Public domain (administration, education, entertainment, services, craftsmen) Da Coatings and paints, thinners, paint removers
Process category PROC7 Industrial sp	
PROC11 Non indust Environmental releas	
ERC8a Widespread ERC8d Widespread	use of non-reactive processing aid (no inclusion into or onto article, indoor) use of non-reactive processing aid (no inclusion into or onto article, outdoor) bstance / the mixture Paint
	plier of the safety data sheet
Manufacturer/Suppli MOTIP DUPLI B.V.	er:
Wolfraamweg 2	
NL- 8471 XC Wolvege	1
<i>The Netherlands</i> <i>Tel:</i> +31 (0)561 6944	100
Fax: +31 (0)561 6944	
e-mail info@nl.motip	dupli.com
	obtainable from: Department Product Safety sone number: +31 (0)561-694400 (09:00h - 17:00h)
SECTION 2: Haz	ards identification
	ards identification he substance or mixture
2.1 Classification of t	· ·
2.1 Classification of t	he substance or mixture ing to Regulation (EC) No 1272/2008
2.1 Classification of t Classification accord GHS02 flar	he substance or mixture ing to Regulation (EC) No 1272/2008
2.1 Classification of t Classification accord GHS02 flar	he substance or mixture ing to Regulation (EC) No 1272/2008 ne
2.1 Classification of the Classification accord GHS02 flant Aerosol 1 H222-H2	he substance or mixture ing to Regulation (EC) No 1272/2008 ne
2.1 Classification of t Classification accord GHS02 flan Aerosol 1 H222-H2	he substance or mixture ing to Regulation (EC) No 1272/2008 ne 29 Extremely flammable aerosol. Pressurised container: May burst if heated.
2.1 Classification of the Classification accord Classification accord GHS02 flan Aerosol 1 H222-H2 GHS07 Eye Irrit. 2 H319	he substance or mixture ing to Regulation (EC) No 1272/2008 ne 29 Extremely flammable aerosol. Pressurised container: May burst if heated. Causes serious eye irritation.

Page 2/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 14.04.2017

Version number 161

Revision: 29.11.2016

GB

Trade name: MOTIP® SEMI GLOSS BLACK 500 ML

	(Contd. of pag
Hazard p	ictograms
$\mathbf{\wedge}$	\wedge
, we	
GHS02	GHS07
011502	011007
Signal wo	o rd Danger
Hazard-d	letermining components of labelling:
acetone	
n-butyl ac	<i>cetate</i>
butan-1-a	bl
propan-2	-ol
Hazard st	tatements
Н222-Н2	29 Extremely flammable aerosol. Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
Precautio	onary statements
P102	Keep out of reach of children.
P260	Do not breathe spray.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P251	Do not pierce or burn, even after use.
P211	Do not spray on an open flame or other ignition source.
P410+P4	12 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container in accordance with local regulations.
Additiond	al information:
	Repeated exposure may cause skin dryness or cracking.
2.3 Other	
Results o	f PBT and vPvB assessment
PBT: Not	t applicable.

· vPvB: Not applicable.

*

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

• Dangerous components:		
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49-xxxx	acetone Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	_ 25-50%
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29-xxxx	n-butyl acetate Flam. Liq. 3, H226 STOT SE 3, H336	_ 12.5-20%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21-xxxx	propane Flam. Gas 1, H220 Press. Gas C, H280	_ 10-12.5%
	()	Contd. on page 3

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 14.04.2017

Version number 161

Revision: 29.11.2016

Trade name: MOTIP® SEMI GLOSS BLACK 500 ML

		ntd. of page
	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226	5-10%
EINECS: 203-448-7	butane Flam. Gas 1, H220 Press. Gas C, H280	5-10%
EINECS: 200-857-2	isobutane Flam. Gas 1, H220 Press. Gas C, H280	5-10%
EINECS: 200-751-6 Index number: 603-004-00-6	 butan-1-ol Flam. Liq. 3, H226 Eye Dam. 1, H318 Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335- H336 	2.5-5%
	nitrocellulose solutions, with not more than 12.6% nitrogen, by dry mass, and not more than 55% nitrocellulose Flam. Sol. 1, H228	1-2.5%
EINECS: 200-661-7	propan-2-ol Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	1-2.5%

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation

Keep away from ignition sources.

(Contd. on page 4)

⁻ GB

Page 4/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 14.04.2017

Version number 161

Revision: 29.11.2016

Trade name: MOTIP® SEMI GLOSS BLACK 500 ML

6.2 Environmental precautions:
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.
6.4 Reference to other sections
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- Observe official regulations on storing packagings with pressurised containers.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Protect from heat and direct sunlight.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

67-64-1 acetone	
WEL Short-term value: 3620 mg/m ³ , 1500 ppm Long-term value: 1210 mg/m ³ , 500 ppm	
123-86-4 n-butyl acetate	
WEL Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm	
108-65-6 2-methoxy-1-methylethyl acetate	
WEL Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm Sk	
106-97-8 butane	
WEL Short-term value: 1810 mg/m ³ , 750 ppm Long-term value: 1450 mg/m ³ , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)	
71-36-3 butan-1-ol	
WEL Short-term value: 154 mg/m ³ , 50 ppm Sk	
	(Contd. on page

Page 5/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 14.04.2017

Version number 161

Revision: 29.11.2016

(Contd. of page 4)

Trade name: MOTIP® SEMI GLOSS BLACK 500 ML

67-63-0 propan-2-ol

WEL Short-term value: 1250 mg/m³, 500 ppm

Long-term value: 999 mg/m³, 400 ppm

· Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

- · Personal protective equipment:
- \cdot General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Do not inhale gases / fumes / aerosols.
- Avoid contact with the eyes.
- Avoid contact with the eyes and skin.
- Respiratory protection: Not required.
- Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

- *Material of gloves* Not required.
- · Penetration time of glove material Not required.
- · Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

• 9.1 Information on basic physical of	and chemical properties
 General Information Appearance: 	
Form:	Aerosol
Colour:	Black
· Odour:	Solvent-like
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Not applicable, as aerosol.
· Flash point:	<0 °C (<32 °F)
-	Not applicable, as aerosol.
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	333 °C (631 °F)
· Decomposition temperature:	Not determined.
· Self-igniting:	Product is not selfigniting.
• Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	1.2 Vol %
Upper:	13.0 Vol %
	(Contd. on page 6

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 14.04.2017

Version number 161

Revision: 29.11.2016

Trade name: MOTIP® SEMI GLOSS BLACK 500 ML

		(Contd. of page 5)
· Vapour pressure at 20 °C (68 °F):	3500 hPa (2625 mm Hg)	
• Density at 20 °C (68 °F):	0.77489 g/cm ³ (6.466 lbs/gal)	
· Relative density	Not determined.	
· Vapour density	Not determined.	
\cdot Evaporation rate	Not applicable.	
· Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/wate	r): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	91.8 %	
· EU-VOC:	712.6 g/l	
• EU-VOC in %:	91.77 %	
· Water:	0.3 %	
· Solids content:	1.4 %	
· 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

67-64-1 ac	etone	
Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	20000 mg/kg (rabbit)
Inhalative	LC50/4 h	39 mg/m3 (rat)
123-86-4 n	ı-butyl aceta	ite
Oral	LD50	10770 mg/kg (rat)
Dermal	LD50	>17600 mg/kg (rabbit)
Inhalative	LC50/4 h	>21.0 mg/m3 (rat)
108-65-62	2-methoxy-1	-methylethyl acetate
Oral	LD50	8532 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rabbit)
Inhalative	LC50/4 h	35.7 mg/m3 (rat)
106-97-8 b	outane	
Inhalative	LC50/4 h	658000 mg/m3 (rat)
		(Contd. on pag

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 14.04.2017

Version number 161

Revision: 29.11.2016

Trade name: MOTIP® SEMI GLOSS BLACK 500 ML

		(Contd. of page 6)
71-36-3 bi	ıtan-1-ol	
Oral	LD50	2292 mg/kg (rat)
Dermal	LD50	3430 mg/kg (rabbit)
Inhalative	LC50/4 h	17.76 mg/m3 (rat)
67-63-0 pr	opan-2-ol	
Oral	LD50	5045 mg/kg (rat)
Dermal	LD50	12800 mg/kg (rabbit)
Inhalative	LC50/4 h	30 mg/m3 (rat)
· Primary ir	ritant effect	
 Skin corro 	sion/irritati	on Based on available data, the classification criteria are not met.
· Serious ey	e damage/ir	ritation
Causes ser	ious eye irri	itation.
· Respirator	y or skin se	nsitisation Based on available data, the classification criteria are not met.

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

• Germ cell mutagenicity Based on available data, the classification criteria are not met.

• Carcinogenicity Based on available data, the classification criteria are not met.

• *Reproductive toxicity Based on available data, the classification criteria are not met.*

· STOT-single exposure

May cause drowsiness or dizziness.

• STOT-repeated exposure Based on available data, the classification criteria are not met.

· Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

Aquatic toxicity:	
67-64-1 acetone	
EC50/48 h	8800 mg/l (daphnia magna)
LC50 / 48 h	2262 mg/l (daphnia magna)
LC50/96 h (static)	5540 mg/l (fish)
123-86-4 n-butyl acetate	
EC50 / 48 h	44 mg/l (daphnia magna)
EC50 / 96 h	320 mg/l (algae)
LC50/24 h	205 mg/l (daphnia magna)
LC50 / 96 h 18 mg/l (Pimephales promelas)	
108-65-6 2-methoxy-1	-methylethyl acetate
EC50 408 mg/l (daphnia magna)	
71-36-3 butan-1-ol	
EC50 / 48 h	1328 mg/l (daphnia magna)
EC50 / 72 h	8500 mg/l (algae)
LC50 / 96 h	1376 mg/l (Pimephales promelas)
67-63-0 propan-2-ol	
EC50 / 48 h	13299 mg/l (daphnia magna)
LC50 / 96 h (dynamic)	4200 mg/l (fish)
12.2 Persistence and a	legradability No further relevant information available.

• 12.4 Mobility in soil No further relevant information available.

(Contd. on page 8)

GB -

Page 8/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 14.04.2017

Version number 161

Revision: 29.11.2016

(Contd. of page 7)

Trade name: MOTIP® SEMI GLOSS BLACK 500 ML

- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

15 01 04 metallic packaging

· Uncleaned packaging:

· Recommendation: Non contaminated packagings may be recycled.

14.1 UN-Number ADR, IMDG, IATA	UN1950	
14.2 UN proper shipping name		
ADR	1950 AEROSOLS	
IMDG	AEROSOLS	
IATA	AEROSOLS, flammable	
14.3 Transport hazard class(es)		
ADR		
Class	2 5F Gases.	
Label	2 57 Gases. 2.1	
IMDG, IATA		
Class	2.1	
Label	2.1	
14.4 Packing group ADR, IMDG, IATA	Void	
14.5 Environmental hazards: Marine pollutant:	No	
14.6 Special precautions for user Danger code (Kemler):	Warning: Gases.	

- GB

Page 9/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 14.04.2017

Version number 161

Revision: 29.11.2016

Trade name: MOTIP® SEMI GLOSS BLACK 500 ML

	(Contd. of page 8)
· EMS Number:	F- D , S - U
· Stowage Code	SW1 Protected from sources of heat.
-	SW22 For AEROSOLS with a maximum capacity of 1 litre:
	Category A. For AEROSOLS with a capacity above 1 litre:
	Category B. For WASTE AEROSOLS: Category C, Clear
	of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre:
	Segregation as for class 9. Stow "separated from" class 1
	except for division 1.4. For AEROSOLS with a capacity
	above 1 litre: Segregation as for the appropriate
	subdivision of class 2. For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class 2.
· 14.7 Transport in bulk according to Anne	ex II of
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
· ADR	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D
IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (\widetilde{EQ})	Code: E0
	Not permitted as Excepted Quantity
· UN ''Model Regulation'':	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases
H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H228 Flammable solid.
H280 Contains gas under pressure; may explode if heated.
H302 Harmful if swallowed.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.

(Contd. on page 10)

GB

Page 10/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 14.04.2017

Version number 161

Revision: 29.11.2016

Trade name: MOTIP® SEMI GLOSS BLACK 500 ML

	(Contd. of page
H336 May cause drowsiness or dizziness.	
Department issuing SDS: R&D legislation and regulatory advisor	
Contact: Mr. K. Smedeman	
Abbreviations and acronyms:	
RID: Règlement international concernant le transport des marchandises dangereuses par chemin	de fer (Regulations Concerning the
International Transport of Dangerous Goods by Rail)	de jei (regulations concerning me
ICAO: International Civil Aviation Organisation	
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agre	eement concerning the International
Carriage of Dangerous Goods by Road)	
IMDG: International Maritime Code for Dangerous Goods	
IATA: International Air Transport Association	
GHS: Globally Harmonised System of Classification and Labelling of Chemicals	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
Flam. Gas 1: Flammable gases – Category 1	
Aerosol 1: Aerosols – Category 1	
Press. Gas C: Gases under pressure – Compressed gas	
Flam. Liq. 2: Flammable liquids – Category 2	
Flam. Liq. 3: Flammable liquids – Category 3	
Flam. Sol. 1: Flammable solids – Category 1	
Acute Tox. 4: Acute toxicity – Category 4	
Skin Irrit. 2: Skin corrosion/irritation – Category 2	
Eye Dam. 1: Serious eye damage/eye irritation – Category 1	
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2	
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	
* Data compared to the previous version altered.	