Page 1/10

*

*



٦



Printing date 14.04.2017

Version number 109

Revision: 14.04.2017

· 1.1 Product identifie	r P® WHEELSPRAY WHITE 500 ML
Article number: 0400 1.2 Relevant identified	ed uses of the substance or mixture and uses advised against
· Sector of Use	
	es: Private households / general public / consumers
	uses: Public domain (administration, education, entertainment, services, craftsmen) 9a Coatings and paints, thinners, paint removers
· Process category	
PROC7 Industrial s	
PROC11 Non indus • Environmental relea	
	use of non-reactive processing aid (no inclusion into or onto article, indoor)
ERC8d Widespread	use of non-reactive processing aid (no inclusion into or onto article, outdoor)
• Application of the su	bstance / the mixture Paint
	pplier of the safety data sheet
• Manufacturer/Suppl MOTIP DUPLI B.V.	ier:
Wolfraamweg 2	
NL- 8471 XC Wolveg	a
The Netherlands $T_{1} \rightarrow 21 (0) 561 604$	400
<i>Tel:</i> +31 (0)561 694 <i>Fax:</i> +31 (0)561 694	
e-mail info@nl.motip	
in the second second	auph.com
· Further information	obtainable from: Department Product Safety hone number: +31 (0)561-694400 (09:00h - 17:00h)
• Further information • 1.4 Emergency telep	obtainable from: Department Product Safety
• Further information • 1.4 Emergency telept SECTION 2: Hay	obtainable from: Department Product Safety hone number: +31 (0)561-694400 (09:00h - 17:00h) zards identification
Further information 1.4 Emergency telepo SECTION 2: Hay 2.1 Classification of	obtainable from: Department Product Safety hone number: +31 (0)561-694400 (09:00h - 17:00h)
Further information 1.4 Emergency telepo SECTION 2: Hay 2.1 Classification of	obtainable from: Department Product Safety hone number: +31 (0)561-694400 (09:00h - 17:00h) zards identification the substance or mixture ling to Regulation (EC) No 1272/2008
 Further information 1.4 Emergency telept SECTION 2: Hax 2.1 Classification of Classification accord GHS02 flat 	obtainable from: Department Product Safety hone number: +31 (0)561-694400 (09:00h - 17:00h) zards identification the substance or mixture ling to Regulation (EC) No 1272/2008
 Further information 1.4 Emergency telept SECTION 2: Hax 2.1 Classification of Classification accord GHS02 flat 	obtainable from: Department Product Safety hone number: +31 (0)561-694400 (09:00h - 17:00h) cards identification the substance or mixture ling to Regulation (EC) No 1272/2008 me
Further information 1.4 Emergency telept SECTION 2: Har 2.1 Classification of Classification accord GHS02 fla Aerosol 1 H222-H2	obtainable from: Department Product Safety hone number: +31 (0)561-694400 (09:00h - 17:00h) cards identification the substance or mixture ling to Regulation (EC) No 1272/2008 me
 Further information 1.4 Emergency telept SECTION 2: Hay 2.1 Classification of Classification accord GHS02 flat Aerosol 1 H222-H2 GHS07 	obtainable from: Department Product Safety hone number: +31 (0)561-694400 (09:00h - 17:00h) cards identification the substance or mixture ling to Regulation (EC) No 1272/2008 me 229 Extremely flammable aerosol. Pressurised container: May burst if heated.
• Further information • 1.4 Emergency telept SECTION 2: Hay • 2.1 Classification of • Classification accord • Classification accord • GHS02 fla Aerosol 1 H222-H2 • GHS07 Eye Irrit. 2 H319	obtainable from: Department Product Safety hone number: +31 (0)561-694400 (09:00h - 17:00h) cards identification the substance or mixture ling to Regulation (EC) No 1272/2008 me 229 Extremely flammable aerosol. Pressurised container: May burst if heated. Causes serious eye irritation.
 Further information 1.4 Emergency teleption SECTION 2: Hay 2.1 Classification accord Classification accord GHS02 flat Aerosol 1 H222-H2 GHS07 Eye Irrit. 2 H319 STOT SE 3 H336 2.2 Label elements Labelling according 	obtainable from: Department Product Safety hone number: +31 (0)561-694400 (09:00h - 17:00h) cards identification the substance or mixture ling to Regulation (EC) No 1272/2008 me 229 Extremely flammable aerosol. Pressurised container: May burst if heated. Causes serious eye irritation.

Page 2/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 14.04.2017

Version number 109

Revision: 14.04.2017

Trade name: MOTIP® WHEELSPRAY WHITE 500 ML

	(Contd. of page
Hazard p	nictograms
^	▲ ▲
بلار	
<u>₹7</u>	
V	
GHS02	GHS07
Signal w	ord Danger
Hazard-a	letermining components of labelling:
acetone	
n-butyl a	cetate
butan-1-	pl
Hazard s	tatements
H222-H2	229 Extremely flammable aerosol. Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
Precauti	onary statements
P102	Keep out of reach of children.
P260	Do not breathe spray.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P251	Do not pierce or burn, even after use.
P211	Do not spray on an open flame or other ignition source.
P410+P4	412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container in accordance with local regulations.
Addition	al information:
	Repeated exposure may cause skin dryness or cracking.
2.3 Other	
Results o	f PBT and vPvB assessment
	t applicable.

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components: CAS: 67-64-1 25-50% acetone Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49-xxxx CAS: 123-86-4 n-butyl acetate 10-12.5% EINECS: 204-658-1 Flam. Liq. 3, H226 STOT SE 3, H336 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29-xxxx CAS: 74-98-6 10-12.5% propane EINECS: 200-827-9 🚯 Flam. Gas 1, H220 Press. Gas C, H280 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21-xxxx CAS: 108-65-6 2-methoxy-1-methylethyl acetate 5-10% EINECS: 203-603-9 📀 Flam. Liq. 3, H226 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29-xxxx (Contd. on page 3)

GB

Printing date 14.04.2017

Version number 109

Revision: 14.04.2017

Trade name: MOTIP® WHEELSPRAY WHITE 500 ML

	(Cor	ntd. of page 2
CAS: 106-97-8	butane	5-10%
EINECS: 203-448-7 Index number: 601-004-00-0	🚸 Flam. Gas 1, H220 Press. Gas C, H280	
Reg.nr.: 01-2119474691-32-xxxx	1 ress. Ous C, 11200	
CAS: 75-28-5	isobutane	5-10%
EINECS: 200-857-2	🚸 Flam. Gas 1, H220	
Index number: 601-004-00-0	Press. Gas C, H280	
Reg.nr.: 01-2119485395-27-xxxx		
CAS: 71-36-3	butan-1-ol	2.5-5%
EINECS: 200-751-6	Flam. Liq. 3, H226	
Index number: 603-004-00-6	Eye Dam. 1, H318	
Reg.nr.: 01-2119484630-38-xxxx	Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335- H336	
CAS: 9004-70-0	nitrocellulose solutions, with not more than 12.6% nitrogen, by	1-2.5%
	dry mass, and not more than 55% nitrocellulose	
	🚸 Flam. Sol. 1, H228	

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- \cdot After skin contact: Generally the product does not irritate the skin.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- \cdot 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation Keep away from ignition sources.
- 6.2 Environmental precautions:
- Do not allow product to reach sewage system or any water course.
- Inform respective authorities in case of seepage into water course or sewage system.
- Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.
- · 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.

(Contd. on page 4)

GB

Page 4/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 14.04.2017

Version number 109

Revision: 14.04.2017

(Contd. of page 3)

Trade name: MOTIP® WHEELSPRAY WHITE 500 ML

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection: Do not spray onto a naked flame or any incandescent material. Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

· 7.2 Conditions for safe storage, including any incompatibilities

- · Storage:
- *Requirements to be met by storerooms and receptacles: Store in a cool location.*

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Protect from heat and direct sunlight.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· 8.1 C	ontrol parameters
· Ingre	dients with limit values that require monitoring at the workplace:
67-64	-1 acetone
WEL	Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm
123-8	6-4 n-butyl acetate
WEL	Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm
108-6	5-6 2-methoxy-1-methylethyl acetate
WEL	Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk
106-9	7-8 butane
WEL	Short-term value: 1810 mg/m ³ , 750 ppm Long-term value: 1450 mg/m ³ , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
71-36	i-3 butan-1-ol
WEL	Short-term value: 154 mg/m³, 50 ppm Sk
· Addit	ional information: The lists valid during the making were used as basis.
· Perso	xposure controls nal protective equipment:
	ral protective and hygienic measures:
Imme Wash	away from foodstuffs, beverages and feed. diately remove all soiled and contaminated clothing hands before breaks and at the end of work.

- Do not inhale gases / fumes / aerosols.
- Avoid contact with the eyes.

Avoid contact with the eyes and skin.

(Contd. on page 5)

GB

Page 5/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 14.04.2017

Version number 109

Revision: 14.04.2017

Trade name: MOTIP® WHEELSPRAY WHITE 500 ML

· Respiratory protection: Not required.

• Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

- · Material of gloves Not required.
- · Penetration time of glove material Not required.
- · Eye protection:



*

Tightly sealed goggles

SECTION 9: Physical and che	emical properties	
• 9.1 Information on basic physical an • General Information	nd chemical properties	
· Appearance: Form:	Aerosol	
Form: Colour:	White	
· Odour:	Solvent-like	
· Odour threshold:	Not determined.	
· pH-value:	Not determined.	
-		
· Change in condition	II. d. t	
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	Not applicable, as aerosol.	
· Flash point:	<0 °C (<32 °F)	
	Not applicable, as aerosol.	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:	333 °C (631 °F)	
· Decomposition temperature:	Not determined.	
· Self-igniting:	Product is not selfigniting.	
• Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.	
· Explosion limits:		
Lower:	1.2 Vol %	
Upper:	13.0 Vol %	
• Vapour pressure at 20 °C (68 °F):	3500 hPa (2625 mm Hg)	
• Density at 20 °C (68 °F):	0.766 g/cm ³ (6.392 lbs/gal)	
· Relative density	Not determined.	
· Vapour density	Not determined.	
• Evaporation rate	Not applicable.	
· Solubility in / Miscibility with	••	
• Solubility in 7 Miscibility with water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/water): Not determined.		
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
	(Contd. on page 6	

(Contd. of page 4)

GE

Printing date 14.04.2017

Version number 109

Revision: 14.04.2017

Trade name: MOTIP® WHEELSPRAY WHITE 500 ML

		(Contd. of page 5)
· Solvent content: Organic solvents:	87.8 %	
· EU-VOC:	674.3 g/l	
• EU-VOC in %: • Water:	87.85 % 0.3 %	
· water:	3.0 %	
• 9.2 Other information	<i>No further relevant information available.</i>	

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- $\cdot \ 10.5 \ Incompatible \ materials: \ No \ further \ relevant \ information \ available.$
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:		
67-64-1 acetone		
LD50	5800 mg/kg (rat)	
LD50	20000 mg/kg (rabbit)	
LC50/4h	39 mg/m3 (rat)	
-butyl aceto	ate	
LD50	10770 mg/kg (rat)	
LD50	>17600 mg/kg (rabbit)	
LC50/4h	>21.0 mg/m3 (rat)	
-methoxy-1	-methylethyl acetate	
LD50	8532 mg/kg (rat)	
LD50	>5000 mg/kg (rabbit)	
LC50/4h	35.7 mg/m3 (rat)	
utane		
LC50/4 h	658000 mg/m3 (rat)	
71-36-3 butan-1-ol		
LD50	2292 mg/kg (rat)	
LD50	3430 mg/kg (rabbit)	
LC50/4 h	17.76 mg/m3 (rat)	
	etone LD50 LD50 LC50 / 4 h -butyl aceta LD50 LD50 LC50 / 4 h -methoxy-1 LD50 LD50 LC50 / 4 h utane LC50 / 4 h tan-1-ol LD50 LD50 LD50	

• Primary irritant effect:

· Skin corrosion/irritation Based on available data, the classification criteria are not met.

 \cdot Serious eye damage/irritation

Causes serious eye irritation.

• Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

· Germ cell mutagenicity Based on available data, the classification criteria are not met.

· Carcinogenicity Based on available data, the classification criteria are not met.

 $\cdot \textit{Reproductive toxicity Based on available data, the classification criteria are not met.}$

(Contd. on page 7)

Printing date 14.04.2017

Version number 109

Revision: 14.04.2017

(Contd. of page 6)

Trade name: MOTIP® WHEELSPRAY WHITE 500 ML

- · STOT-single exposure
- May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxic	city
--------------	------

• Aquatic toxicity:			
67-64-1 acetone			
EC50 / 48 h	8800 mg/l (daphnia magna)		
LC50 / 48 h	2262 mg/l (daphnia magna)		
LC50 / 96 h (static)	5540 mg/l (fish)		
123-86-4 n-butyl ac	123-86-4 n-butyl acetate		
EC50 / 48 h	44 mg/l (daphnia magna)		
EC50 / 96 h	320 mg/l (algae)		
LC50 / 24 h	205 mg/l (daphnia magna)		
LC50 / 96 h	18 mg/l (Pimephales promelas)		
108-65-6 2-methoxy-1-methylethyl acetate			
EC50	408 mg/l (daphnia magna)		
71-36-3 butan-1-ol	71-36-3 butan-1-ol		
EC50 / 48 h	1328 mg/l (daphnia magna)		

EC50 / 72 h	8500 mg/l (algae)
-------------	-------------------

LC50 / 96 h 1376 mg/l (Pimephales promelas)

· 12.2 Persistence and degradability No further relevant information available.

- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.

· Additional ecological information:

· General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· 12.5 Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· vPvB: Not applicable.

· 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

 \cdot European waste catalogue

08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

15 01 04 metallic packaging

· Uncleaned packaging:

· Recommendation: Non contaminated packagings may be recycled.

(Contd. on page 8)

Page 8/10

*

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 14.04.2017

Version number 109

Revision: 14.04.2017

Trade name: MOTIP® WHEELSPRAY WHITE 500 ML

(Contd. of page 7)

14.1 UN-Number	
ADR, IMDG, IATA	UN1950
14.2 UN proper shipping name	
ADR	1950 AEROSOLS
IMDG	AEROSOLS
IATA	AEROSOLS, flammable
14.3 Transport hazard class(es)	
ADR	
Class	2 5F Gases.
Label	2.1
IMDG, IATA	
2	
Class	2.1
Label	2.1
14.4 Packing group ADR, IMDG, IATA	Void
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Warning: Gases.
Danger code (Kemler):	-
EMS Number:	F-D,S-U
Stowage Code	SW1 Protected from sources of heat.
	SW22 For AEROSOLS with a maximum capacity of 1 lit
	Category A. For AEROSOLS with a capacity above 1 lit
	Category B. For WASTE AEROSOLS: Category C, Clea
Sugregation Code	of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 lith
	Segregation as for class 9. Stow "separated from" class except for division 1.4. For AEROSOLS with a capacity
	above 1 litre: Segregation as for the appropriate
	subdivision of class 2. For WASTE AEROSOLS:
	Subdivision of class 2. For waste AEROSOLS. Segregation as for the appropriate subdivision of class 2
14.7 Transport in bulk according to Anno Marpol and the IBC Code	
Transport/Additional information:	
· · · · · · · · · · · · · · · · · · ·	
ADR Limited an antities (LO)	11
Limited quantities (LQ)	IL Code: F0
Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
Transport category	Not permitted as Excepted Quantity 2
Tunnel restriction code	$\overset{2}{D}$

Printing date 14.04.2017

Version number 109

Revision: 14.04.2017

Trade name: MOTIP® WHEELSPRAY WHITE 500 ML

		(Contd. of page 8)
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity	
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1	

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P3a FLAMMABLE AEROSOLS

 \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t

 \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas. H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H228 Flammable solid.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

· Department issuing SDS: R&D legislation and regulatory advisor

· Contact: Mr. K. Smedeman

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative Flam. Gas 1: Flammable gases – Category 1

Aerosol 1: Aerosols – Category 1

Press. Gas C: Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids - Category 2

Flam. Liq. 3: Flammable liquids – Category 3

- Flam. Sol. 1: Flammable solids Category 1
- Acute Tox. 4: Acute toxicity Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation – Category 1

(Contd. on page 10)

Page 10/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 14.04.2017

Version number 109

Revision: 14.04.2017

Trade name: MOTIP® WHEELSPRAY WHITE 500 ML

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 • * *Data compared to the previous version altered.* (Contd. of page 9)

GB