

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 14.04.2017

Version number 19

Revision: 17.02.2016

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

- **1.1 Product identifier**
- **Trade name:** MOTIP® TUNING LINE ENGINE PAINT ALUMINIUM 400 ML
- **Article number:** 04093
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use**  
 SU21 Consumer uses: Private households / general public / consumers  
 SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Product category** PC9a Coatings and paints, thinners, paint removers
- **Process category**  
 PROC7 Industrial spraying  
 PROC11 Non industrial spraying
- **Environmental release category**  
 ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)  
 ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)
- **Application of the substance / the mixture** Spray varnish
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
 MOTIP DUPLI B.V.  
 Wolfraamweg 2  
 NL- 8471 XC Wolvega  
 The Netherlands  
 Tel: +31 (0)561 694400  
 Fax: +31 (0)561 694411  
 e-mail info@nl.motipdupli.com
- **Further information obtainable from:** Department Product Safety
- **1.4 Emergency telephone number:** +31 (0)561-694400 (09:00h - 17:00h)

**SECTION 2: Hazards identification**

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Aerosol 1                      H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS07

Eye Irrit. 2                      H319                      Causes serious eye irritation.

STOT SE 3                      H336                      May cause drowsiness or dizziness.

Aquatic Chronic 3                      H412                      Harmful to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
 The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 14.04.2017

Version number 19

Revision: 17.02.2016

Trade name: **MOTIP® TUNING LINE ENGINE PAINT ALUMINIUM 400 ML**

(Contd. of page 1)

· **Hazard pictograms**

GHS02 GHS07

· **Signal word** Danger· **Hazard-determining components of labelling:**

acetone

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Solvent naphtha (petroleum), light arom.

· **Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

P102 Keep out of reach of children.

P260 Do not breathe spray.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P211 Do not spray on an open flame or other ignition source.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local regulations.

· **Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

· **2.3 Other hazards**· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

· **3.2 Chemical characterisation: Mixtures**· **Description:** Mixture of substances listed below with nonhazardous additions.· **Dangerous components:**

CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49-xxxx	acetone ----- Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	25-50%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21-xxxx	propane ----- Flam. Gas 1, H220 Press. Gas C, H280	12.5-20%
EC number: 919-446-0 Reg.nr.: 01-2119458049-33-xxxx	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) ----- Flam. Liq. 3, H226 STOT RE 1, H372; Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H336	12.5-20%

(Contd. on page 3)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 14.04.2017

Version number 19

Revision: 17.02.2016

Trade name: **MOTIP® TUNING LINE ENGINE PAINT ALUMINIUM 400 ML**

(Contd. of page 2)

CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32-xxxx	butane ----- ☠ Flam. Gas 1, H220 Press. Gas C, H280	10-12.5%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27-xxxx	isobutane ----- ☠ Flam. Gas 1, H220 Press. Gas C, H280	10-12.5%
EC number: 918-668-5 Reg.nr.: 01-2119455851-35-xxxx	Solvent naphtha (petroleum), light arom. ----- ☠ Flam. Liq. 3, H226 ☠ Asp. Tox. 1, H304 ☠ Aquatic Chronic 2, H411 ☠ STOT SE 3, H335-H336	1-2.5%
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32-xxxx	xylene ----- ☠ Flam. Liq. 3, H226 ☠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	1-2.5%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

#### **SECTION 4: First aid measures**

- **4.1 Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

#### **SECTION 5: Firefighting measures**

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

#### **SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Ensure adequate ventilation  
Keep away from ignition sources.
- **6.2 Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.

(Contd. on page 4)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 14.04.2017

Version number 19

Revision: 17.02.2016

Trade name: MOTIP® TUNING LINE ENGINE PAINT ALUMINIUM 400 ML

See Section 13 for disposal information.

(Contd. of page 3)

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**  
Do not spray onto a naked flame or any incandescent material.  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Store in a cool location.  
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Protect from heat and direct sunlight.
- **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

#### · 8.1 Control parameters

- **Ingredients with limit values that require monitoring at the workplace:**

##### 67-64-1 acetone

WEL	Short-term value: 3620 mg/m <sup>3</sup> , 1500 ppm Long-term value: 1210 mg/m <sup>3</sup> , 500 ppm
-----	----------------------------------------------------------------------------------------------------------

##### 106-97-8 butane

WEL	Short-term value: 1810 mg/m <sup>3</sup> , 750 ppm Long-term value: 1450 mg/m <sup>3</sup> , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
-----	-------------------------------------------------------------------------------------------------------------------------------------------------------

##### 1330-20-7 xylene

WEL	Short-term value: 441 mg/m <sup>3</sup> , 100 ppm Long-term value: 220 mg/m <sup>3</sup> , 50 ppm Sk; BMGV
-----	------------------------------------------------------------------------------------------------------------------

- **Ingredients with biological limit values:**

##### 1330-20-7 xylene

BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
------	----------------------------------------------------------------------------------------------------------

- **Additional information:** The lists valid during the making were used as basis.

#### · 8.2 Exposure controls

- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.  
Avoid contact with the eyes.  
Avoid contact with the eyes and skin.

(Contd. on page 5)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 14.04.2017

Version number 19

Revision: 17.02.2016

Trade name: MOTIP® TUNING LINE ENGINE PAINT ALUMINIUM 400 ML

(Contd. of page 4)

- **Respiratory protection:** Not required.
- **Protection of hands:** Not required.
- **Material of gloves:** Not required.
- **Penetration time of glove material:** Not required.
- **Eye protection:**



Tightly sealed goggles

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### General Information

#### Appearance:

- |                           |                 |
|---------------------------|-----------------|
| · <b>Form:</b>            | Aerosol         |
| · <b>Colour:</b>          | Silver-coloured |
| · <b>Odour:</b>           | Solvent-like    |
| · <b>Odour threshold:</b> | Not determined. |

- |                    |                 |
|--------------------|-----------------|
| · <b>pH-value:</b> | Not determined. |
|--------------------|-----------------|

#### Change in condition

- |                                       |                             |
|---------------------------------------|-----------------------------|
| · <b>Melting point/Melting range:</b> | Undetermined.               |
| · <b>Boiling point/Boiling range:</b> | Not applicable, as aerosol. |

- |                       |                                               |
|-----------------------|-----------------------------------------------|
| · <b>Flash point:</b> | <0 °C (<32 °F)<br>Not applicable, as aerosol. |
|-----------------------|-----------------------------------------------|

- |                                         |                 |
|-----------------------------------------|-----------------|
| · <b>Flammability (solid, gaseous):</b> | Not applicable. |
|-----------------------------------------|-----------------|

- |                                |                     |
|--------------------------------|---------------------|
| · <b>Ignition temperature:</b> | > 200 °C (> 392 °F) |
|--------------------------------|---------------------|

- |                                     |                 |
|-------------------------------------|-----------------|
| · <b>Decomposition temperature:</b> | Not determined. |
|-------------------------------------|-----------------|

- |                         |                              |
|-------------------------|------------------------------|
| · <b>Self-igniting:</b> | Product is not selfigniting. |
|-------------------------|------------------------------|

- |                               |                                                                                             |
|-------------------------------|---------------------------------------------------------------------------------------------|
| · <b>Danger of explosion:</b> | Product is not explosive. However, formation of explosive air/vapour mixtures are possible. |
|-------------------------------|---------------------------------------------------------------------------------------------|

#### Explosion limits:

- |                 |            |
|-----------------|------------|
| · <b>Lower:</b> | 0.6 Vol %  |
| · <b>Upper:</b> | 13.0 Vol % |

- |                                            |                       |
|--------------------------------------------|-----------------------|
| · <b>Vapour pressure at 20 °C (68 °F):</b> | 3500 hPa (2625 mm Hg) |
|--------------------------------------------|-----------------------|

- |                                    |                                         |
|------------------------------------|-----------------------------------------|
| · <b>Density at 20 °C (68 °F):</b> | 0.705 g/cm <sup>3</sup> (5.883 lbs/gal) |
|------------------------------------|-----------------------------------------|

- |                           |                 |
|---------------------------|-----------------|
| · <b>Relative density</b> | Not determined. |
|---------------------------|-----------------|

- |                         |                 |
|-------------------------|-----------------|
| · <b>Vapour density</b> | Not determined. |
|-------------------------|-----------------|

- |                           |                 |
|---------------------------|-----------------|
| · <b>Evaporation rate</b> | Not applicable. |
|---------------------------|-----------------|

#### Solubility in / Miscibility with water:

Not miscible or difficult to mix.

- |                                                   |                 |
|---------------------------------------------------|-----------------|
| · <b>Partition coefficient (n-octanol/water):</b> | Not determined. |
|---------------------------------------------------|-----------------|

#### Viscosity:

- |                     |                 |
|---------------------|-----------------|
| · <b>Dynamic:</b>   | Not determined. |
| · <b>Kinematic:</b> | Not determined. |

#### Solvent content:

- |                            |           |
|----------------------------|-----------|
| · <b>Organic solvents:</b> | 84.6 %    |
| · <b>EU-VOC:</b>           | 596.2 g/l |

(Contd. on page 6)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 14.04.2017

Version number 19

Revision: 17.02.2016

Trade name: MOTIP® TUNING LINE ENGINE PAINT ALUMINIUM 400 ML

(Contd. of page 5)

· <b>EU-VOC in %:</b>	84.57 %
· <b>Solids content:</b>	19.6 %
· <b>9.2 Other information</b>	No further relevant information available.

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

**67-64-1 acetone**

Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	20000 mg/kg (rabbit)
Inhalative	LC50 / 4 h	39 mg/m <sup>3</sup> (rat)

**Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)**

Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	3400 mg/kg (rabbit)
Inhalative	LC50 / 4 h	13100 mg/m <sup>3</sup> (rat)

**106-97-8 butane**

Inhalative	LC50 / 4 h	658000 mg/m <sup>3</sup> (rat)
------------	------------	--------------------------------

**Solvent naphtha (petroleum), light arom.**

Oral	LD50	3592 mg/kg (rat) (OECD401)
Dermal	LD50	>3160 mg/kg (rab) (OECD402)
Inhalative	LC50 / 4 h	>6193 mg/m <sup>3</sup> (rat)

**1330-20-7 xylene**

Oral	LD50	3523 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50 / 4 h	22.1 mg/m <sup>3</sup> (rat)

**64742-48-9 Naphtha (petroleum), hydrotreated heavy**

Oral	LD50	>15000 mg/kg (rat)
Dermal	LD50	>3000 mg/kg (rab)
Inhalative	LC50 / 4 h	>2.8 mg/m <sup>3</sup> (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation**  
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.

(Contd. on page 7)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 14.04.2017

Version number 19

Revision: 17.02.2016

Trade name: MOTIP® TUNING LINE ENGINE PAINT ALUMINIUM 400 ML

(Contd. of page 6)

- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**  
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Aquatic toxicity:

##### 67-64-1 acetone

EC50 / 48 h 8800 mg/l (daphnia magna)

LC50 / 48 h 2262 mg/l (daphnia magna)

LC50 / 96 h (static) 5540 mg/l (fish)

##### Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

EC50 / 48 h 10-22 mg/l (daphnia magna)

EC50 / 72 h 4.6-10 mg/l (algae)

LC50 / 96 h 10-30 mg/l (fish)

##### Solvent naphtha (petroleum), light arom.

EC50 / 24 h 150 mg/l (daphnia magna)

EC50 / 48 h 7.4 mg/l (daphnia magna)

LC50 / 96 h 3.77 mg/l (fish)

##### 1330-20-7 xylene

EC50 / 48 h 7.4 mg/l (daphnia magna)

LC50 / 96 h 13.5 mg/l (fish)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

#### Ecotoxicological effects:

· **Remark:** Harmful to fish

#### Additional ecological information:

#### General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

#### 12.5 Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **12.6 Other adverse effects** No further relevant information available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

#### European waste catalogue

08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
15 01 04	metallic packaging

(Contd. on page 8)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 14.04.2017

Version number 19



Revision: 17.02.2016

Trade name: MOTIP® TUNING LINE ENGINE PAINT ALUMINIUM 400 ML

(Contd. of page 7)

- **Uncleaned packaging:**
- **Recommendation:** Non contaminated packagings may be recycled.

### SECTION 14: Transport information

· <b>14.1 UN-Number</b> · <b>ADR, IMDG, IATA</b>	UN1950
· <b>14.2 UN proper shipping name</b> · <b>ADR</b> · <b>IMDG</b> · <b>IATA</b>	1950 AEROSOLS AEROSOLS AEROSOLS, flammable
· <b>14.3 Transport hazard class(es)</b> · <b>ADR</b>	
	
· <b>Class</b> · <b>Label</b>	2 5F Gases. 2.1
· <b>IMDG, IATA</b>	
	
· <b>Class</b> · <b>Label</b>	2.1 2.1
· <b>14.4 Packing group</b> · <b>ADR, IMDG, IATA</b>	Void
· <b>14.5 Environmental hazards:</b> · <b>Marine pollutant:</b>	No
· <b>14.6 Special precautions for user</b> · <b>Danger code (Kemler):</b> · <b>EMS Number:</b> · <b>Stowage Code</b>	Warning: Gases. - F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· <b>Segregation Code</b>	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>ADR</b> · <b>Limited quantities (LQ)</b>	1L

(Contd. on page 9)

GB



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 14.04.2017

Version number 19

Revision: 17.02.2016

Trade name: **MOTIP® TUNING LINE ENGINE PAINT ALUMINIUM 400 ML**

(Contd. of page 8)

· <b>Excepted quantities (EQ)</b>	Code: E0 Not permitted as Excepted Quantity
· <b>Transport category</b>	2
· <b>Tunnel restriction code</b>	D
-----	
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	IL
· <b>Excepted quantities (EQ)</b>	Code: E0 Not permitted as Excepted Quantity
· <b>UN "Model Regulation":</b>	UN 1950 AEROSOLS, 2.1

**SECTION 15: Regulatory information**

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P3a** FLAMMABLE AEROSOLS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**SECTION 16: Other information**

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

- **Relevant phrases**  
H220 Extremely flammable gas.  
H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H280 Contains gas under pressure; may explode if heated.  
H304 May be fatal if swallowed and enters airways.  
H312 Harmful in contact with skin.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H372 Causes damage to organs through prolonged or repeated exposure.  
H411 Toxic to aquatic life with long lasting effects.
- **Department issuing SDS:** R&D legislation and regulatory advisor
- **Contact:** Mr. K. Smedeman
- **Abbreviations and acronyms:**  
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
ICAO: International Civil Aviation Organisation  
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
Flam. Gas 1: Flammable gases – Category 1

(Contd. on page 10)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 14.04.2017

Version number 19

Revision: 17.02.2016

**Trade name: MOTIP® TUNING LINE ENGINE PAINT ALUMINIUM 400 ML**

(Contd. of page 9)

*Aerosol 1: Aerosols – Category 1**Press. Gas C: Gases under pressure – Compressed gas**Flam. Liq. 2: Flammable liquids – Category 2**Flam. Liq. 3: Flammable liquids – Category 3**Acute Tox. 4: Acute toxicity – Category 4**Skin Irrit. 2: Skin corrosion/irritation – Category 2**Eye Irrit. 2: Serious eye damage/eye irritation – Category 2**STOT SE 3: Specific target organ toxicity (single exposure) – Category 3**STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1**Asp. Tox. 1: Aspiration hazard – Category 1**Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2**Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3***· \* Data compared to the previous version altered.**

GB