Page 1/8



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 14.04.2017

Version number 75

Revision: 22.02.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking · 1.1 Product identifier · Trade name: MOTIP® CUT & DRILL LUBRICANT 500 ML · Article number: 090407 · 1.2 Relevant identified uses of the substance or mixture and uses advised against · Sector of Use SU21 Consumer uses: Private households / general public / consumers SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) · Product category PC25 Metal working fluids · Process category **PROC7** Industrial spraving **PROC11** Non industrial spraving · Environmental release category ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) · Application of the substance / the mixture Lubricant \cdot 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: MOTIP DUPLI B.V. Wolfraamweg 2 NL- 8471 XC Wolvega The Netherlands Tel: +31 (0)561 694400 Fax: +31 (0)561 694411 e-mail info@nl.motipdupli.com · Further information obtainable from: Department Product Safety · 1.4 Emergency telephone number: +31 (0)561-694400 (09:00h - 17:00h) **SECTION 2: Hazards identification** · 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008 GHS02 flame Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. · 2.2 Label elements · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. · Hazard pictograms GHS02 · Signal word Danger · Hazard statements H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. · Precautionary statements P102 Keep out of reach of children. P260 Do not breathe spray.

Page 2/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 14.04.2017

Version number 75

Revision: 22.02.2017

Trade name: MOTIP® CUT & DRILL LUBRICANT 500 ML

- (Contd. of page 1) P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P251 Do not pierce or burn, even after use.

P211 Do not spray on an open flame or other ignition source.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local regulations.

 \cdot 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

• **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

Distillates (petroleum), hydrotreated light paraffinic	20-25%
Naphta (petroleum), hydrotreated heavy 🚸 Asp. Tox. 1, H304	12.5-20%
propane Flam. Gas 1, H220 Press. Gas C, H280	12.5-20%
butane Flam. Gas 1, H220 Press. Gas C, H280	5-10%
isobutane Flam. Gas 1, H220 Press. Gas C, H280	5-10%
	 Asp. Tox. 1, H304 Naphta (petroleum), hydrotreated heavy Asp. Tox. 1, H304 propane Flam. Gas 1, H220 Press. Gas C, H280 butane Flam. Gas 1, H220 Press. Gas C, H280 isobutane Flam. Gas 1, H220

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· After inhalation: Supply fresh air; consult doctor in case of complaints.

· After skin contact: Generally the product does not irritate the skin.

• After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

• After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.

• 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

• 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.

 $(Contd. \ on \ page \ 3)$

⁻ GB

Page 3/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 14.04.2017

Version number 75

Revision: 22.02.2017

Trade name: MOTIP® CUT & DRILL LUBRICANT 500 ML

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation Keep away from ignition sources.
6.2 Environmental precautions: Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.

• 6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

No special measures required.

Ensure good ventilation/exhaustion at the workplace.

- Information about fire and explosion protection: Do not spray onto a naked flame or any incandescent material. Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
 Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
- · 7.2 Conditions for safe storage, including any incompatibilities

• Storage:

• *Requirements to be met by storerooms and receptacles: Store in a cool location.*

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Protect from heat and direct sunlight.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

106-97-8 butane

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm

Carc (if more than 0.1% of buta-1.3-diene)

• Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:
- Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

(Contd. on page 4)

(Contd. of page 2)

GB

Page 4/8

*

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 14.04.2017

Version number 75

Revision: 22.02.2017

(Contd. of page 3)

Trade name: MOTIP® CUT & DRILL LUBRICANT 500 ML

· Respiratory protection: Not required.

• Protection of hands: Not required.

· Material of gloves Not required.

· Penetration time of glove material Not required.

• Eye protection: Not required.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical an	nd chemical properties
· General Information	
· Appearance:	
Form:	Aerosol
Colour:	Light yellow
· Odour:	Mineral-oil-like
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Not applicable, as aerosol.
· Flash point:	<0 °C (<32 °F)
	Not applicable, as aerosol.
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	$> 200 \ ^{\circ}C \ (> 392 \ ^{\circ}F)$
• Decomposition temperature:	Not determined.
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapou mixtures are possible.
· Explosion limits:	
Lower:	0.6 Vol %
Upper:	10.9 Vol %
· Vapour pressure at 20 °C (68 °F):	3500 hPa (2625 mm Hg)
· Density at 20 °C (68 °F):	0.735 g/cm ³ (6.134 lbs/gal)
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water	r): Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	50.0 %
· EU-VOC:	367.5 g/l
• EU-VOC in %:	50.00 %
• 9.2 Other information	No further relevant information available.

(Contd. on page 5)

Page 5/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 14.04.2017

Version number 75

Revision: 22.02.2017

Trade name: MOTIP® CUT & DRILL LUBRICANT 500 ML

(Contd. of page 4)

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

• 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

Nanhta	(netroleum)	hydrotreated heavy
rupnu	(penoieum),	

Oral	LD50	>15000 mg/kg (rat)
Dermal		>3000 mg/kg (rab)
Inhalative		>2.8 mg/m3 (rat)

106-97-8 butane

Inhalative LC50 / 4 h 658000 mg/m3 (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- \cdot Carcinogenicity Based on available data, the classification criteria are not met.
- $\cdot \textit{Reproductive toxicity Based on available data, the classification criteria are not met.}$
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- \cdot Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

3

• Aquatic toxicity:

Naphta (petroleum), hydrotreated heavy

LC50 / 96 h >100 mg/l (crustacean (amphipod))

>100 mg/l (fish)

- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:

· General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· 12.5 Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- · vPvB: Not applicable.

(Contd. on page 6)

GB

Page 6/8

*

*

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 14.04.2017

Version number 75

Revision: 22.02.2017

Trade name: MOTIP® CUT & DRILL LUBRICANT 500 ML

· 12.6 Other adverse effects No further relevant information available.

(Contd. of page 5)

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · European waste catalogue
- 20 01 13* solvents

15 01 04 metallic packaging

· Uncleaned packaging:

· Recommendation: Non contaminated packagings may be recycled.

· 14.1 UN-Number · ADR, IMDG, IATA	UN1950
14.2 UN proper shipping name ADR IMDG IATA	1950 AEROSOLS AEROSOLS AEROSOLS, flammable
· 14.3 Transport hazard class(es)	
· ADR	
· Class	2 5F Gases.
· Label	2.1
· Class · Label	2.1 2.1
· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user	Warning: Gases.
· Danger code (Kemler): · EMS Number:	- F-D,S-U
· Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre Category A. For AEROSOLS with a capacity above 1 litre Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 14.04.2017

Version number 75

Revision: 22.02.2017

GB

Trade name: MOTIP® CUT & DRILL LUBRICANT 500 ML

	(Contd. of page 6
	above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· 14.7 Transport in bulk according to Anne	ex II of
Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
$\cdot ADR$	
\cdot Limited quantities (LQ)	1L
\cdot Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
· Transport category	2
• Tunnel restriction code	D
· IMDG	
\cdot Limited quantities (LQ)	1L
· Excepted quantities (\widetilde{EQ})	Code: E0
• • • • •	Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.H280 Contains gas under pressure; may explode if heated.H304 May be fatal if swallowed and enters airways.

· Department issuing SDS: R&D legislation and regulatory advisor

· Contact: Mr. K. Smedeman · Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1: Flammable gases - Category 1 Aerosol 1: Aerosols - Category 1 (Contd. on page 8) Page 8/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 14.04.2017

Version number 75

Revision: 22.02.2017

Trade name: MOTIP® CUT & DRILL LUBRICANT 500 ML

Press. Gas C: Gases under pressure – Compressed gas Asp. Tox. 1: Aspiration hazard – Category 1 • * Data compared to the previous version altered. (Contd. of page 7)

GB